

Technical Data Sheet

n. 03 [March 2025]

Automatic Turntable Dispensers

COROB T100 [S]



BASE DISPENSER FEATURES

Dispensing technology	NoPurge Piston pump (NPP)
Dispensing flow	Sequential Turntable (Bidirectional)
Dispensing displacement	Internal head
Canister sizes [l] (q-G)	1.5 (1.58) / 2.3 (2.4)
Canister configuration	up to 16
Canister material	POM (Acetalic resin)
Canister stirring	Pre-set [one for all canisters]
Pump type	NPP300P - Pump volume [ml]: 50
Circuit flow rate [l/min]*	0.3
Minimum dispensed quantity [fl.oz.] (cc)*	1/576 (0.051)
Valve type	Sphere valve
Cleaning system	Passive cleaning brush
Electronic generation/type	5G TTD
Colorant base compatibility	Decorative and Industrial: Water [w], Universal and Solvent [s]
User interface	Control devices & Led indicators
Shelf type	Manual "pull out"

DISPENSER VERSIONS

Panels	Sheet Metal / Plastic
External modules add-ons	No
Available versions	[L]

CAN HANDLING FEATURES**

Minimum can height [mm] (in)	70 (2.76)
Maximum can height [mm] (in)	457 (18)
Minimum can diameter [mm] (in)	60 (2.36)
Maximum can diameter [mm] (in)	330 (13) [w/ hole in the center] - 280 (11) [w/ hole not in the center]
Maximum can weight on shelf [kg] (lbs)	35 (77)

POWER SUPPLY / MACHINE ENVIRONMENT

Power supply [V]	Single phase 100 - 240 ±10%
Frequency [Hz]	50/60
Fuses [A]	F 10 A
Maximum power absorption [W]	from 60 to 300 based on the configuration
Working temperature [Celsius] (Fahrenheit)	From 10° to 40° (50° to 104°)
Relative humidity	From 5% to 85% (without condensation)
Certification	CE/UKCA

DISPENSER DIMENSIONS

Length [mm] (in)	670 (26.4)
Depth [mm] (in)	770 (30.2)
Height [mm] (in)	1325 (52.2)
Footprint [m²] (ft²)	0.51 (5.5)
Machine Weight [kg] (lbs)	115 (253.5)
Machine + packaging Weight [kg] (lbs)	140 (308.6)

EQUIPMENT FEATURES

TOUCHcontol	--
Semi-Automatic shelf	--
Semi-Automatic puncher	--
Laser BHL	Optional
Internal heater	Optional
Central monitor support	--
Tablet support	Optional
Corob Connect	Optional

* Values highly affected by the nature of the colorants and their rheological properties.
** IMPORTANT: most machine and paint can dimensions refer to the basic machine model.
Options and alternative devices can change these values. Please check with your local sales representative or contact one of COROB's offices.
Take note: data refers to base configuration machine, figures may vary according to different specifications.
Product not available for China market.
© COPYRIGHT 2025, COROB S.p.A. - All rights reserved in all countries
This information is provided without warranty, representation, inducement or license of any kind. It is accurate to the best COROB's knowledge or is obtained from sources believed to be accurate. COROB therefore assumes no legal responsibility for reliance upon given information.

Technical Data Sheet

n. 03 [March 2025]

Automatic Turntable Dispensers

COROB T100 [L]



BASE DISPENSER FEATURES

Dispensing technology	NoPurge Piston pump (NPP)
Dispensing flow	Sequential Turntable (Bidirectional)
Dispensing displacement	Internal head
Canister sizes [l] (q-G)	1.5 (1.58) / 2.3 (2.4)
Canister configuration	up to 32
Canister material	POM (Acetalic resin)
Canister stirring	Pre-set [one for all canisters]
Pump type	NPP300P - Pump volume [ml]: 50
Circuit flow rate [l/min]*	0.3
Minimum dispensed quantity [fl.oz.] (cc)*	1/576 (0.051)
Valve type	Sphere valve
Cleaning system	Passive cleaning brush
Electronic generation/type	5G TTD
Colorant base compatibility	Decorative and Industrial: Water [w], Universal and Solvent [s]
User interface	Control devices & Led indicators
Shelf type	Manual "pull out"

DISPENSER VERSIONS

Panels	Sheet Metal / Plastic
External modules add-ons	No
Available versions	[S]

CAN HANDLING FEATURES**

Minimum can height [mm] (in)	70 (2.76)
Maximum can height [mm] (in)	457 (18)
Minimum can diameter [mm] (in)	60 (2.36)
Maximum can diameter [mm] (in)	330 (13) [w/ hole in the center] - 280 (11) [w/ hole not in the center]
Maximum can weight on shelf [kg] (lbs)	35 (77)

POWER SUPPLY / MACHINE ENVIRONMENT

Power supply [V]	Single phase 100 - 240 ±10%
Frequency [Hz]	50/60
Fuses [A]	F 10 A
Maximum power absorption [W]	from 60 to 300 based on the configuration
Working temperature [Celsius] (Fahrenheit)	From 10° to 40° (50° to 104°)
Relative humidity	From 5% to 85% (without condensation)
Certification	CE/UKCA

DISPENSER DIMENSIONS

Length [mm] (in)	840 (33)
Depth [mm] (in)	940 (37)
Height [mm] (in)	1325 (52.2)
Footprint [m²] (ft²)	0.79 (8.5)
Machine Weight [kg] (lbs)	166 (366)
Machine + packaging Weight [kg] (lbs)	200 (441)

EQUIPMENT FEATURES

TOUCHcontol	--
Semi-Automatic shelf	--
Semi-Automatic puncher	--
Laser BHL	Optional
Internal heater	Optional
Central monitor support	--
Tablet support	Optional
Corob Connect	Optional

* Values highly affected by the nature of the colorants and their rheological properties.
** IMPORTANT: most machine and paint can dimensions refer to the basic machine model.
Options and alternative devices can change these values. Please check with your local sales representative or contact one of COROB's offices.
Take note: data refers to base configuration machine, figures may vary according to different specifications.
Product not available for China market.
© COPYRIGHT 2025, COROB S.p.A. - All rights reserved in all countries
This information is provided without warranty, representation, inducement or license of any kind. It is accurate to the best COROB's knowledge or is obtained from sources believed to be accurate. COROB therefore assumes no legal responsibility for reliance upon given information.